

WATER MANAGEMENT

GREYCOAT EPOXY



**100% SOLIDS
EPOXY COATING**

100% SOLIDS EPOXY COATING

GreyCoat Epoxy is a premium 100% solids epoxy that offers outstanding chemical resistance and lasting durability with adhesion to concrete substrates and metal surfaces. Prepackaged as a no mess plural component coating system that offers excellent coverage and is shrink resistant. GreyCoat is excellent for rehabilitating a manhole bench or structural spot repair. The epoxy can build up to ¼ inch (250 mils) without sag and exceeds the most demanding engineered specifications.

APPLICATION ADVANTAGES

- Unique two-part bagging system reduces product waste
- Patent pending delivery method
- Smaller packaging allows easier application in limited space conditions
- Designed for structural repair of manholes, wet wells, vaults and more
- Protect against H₂S, other chemicals and gases found in sewer systems
- Viscosity allows installation on vertical and overhead surfaces
- 100% solid monolithic structural epoxy
- Adds structural integrity to repair area
- 15 minute working time @ 70° F, 30 minute set time, 24-hour final cure time
- Wet film thickness will equal dry film thickness
- May be applied at temperatures between 40° F and 120° F
- Superior adhesion in damp humid areas and surfaces
- Applied to a variety of substrates



ENVIRONMENTAL ADVANTAGES

- Zero VOC
- Zero CFCs or HFCs
- Solvent free
- Zero shrinkage
- No environmental leaching
- Odorless
- Less Waste



Part Number	Description	Case Pack
GCE-6KIT	GreyCoat Epoxy Kit- 6 sq.ft. coverage	1
GCE-18KIT	GreyCoat Epoxy- 18 sq.ft. coverage: (6) bagged resin, (8) gloves, (6) scrapers	1
GCE-18BULK	GreyCoat Epoxy- 18 sq.ft.: 1 gal. part A, 1/2 gal. part B	1



Single and multiple component repairs for any situation!



Your 1 Source for Infrastructure
& Water Management Solutions

(877) 450-3701 • www.S1Eonline.com