



QUAD-PLUG™ TECHNICAL DATA SHEET

Rev. 08-2017



**REPAIR
MATERIALS**

Typical Performance Characteristics

- Compressive Strength
STRENGTH - PSI (MPa) (ASTM C109)
30 min. >3000 psi
- Bond Strength (ASTM C321)
28 day >500 psi

RECOMMENDED FOR

- Sewer Pipes and Manholes
- Concrete Tanks
- Elevator Pits
- Cisterns
- Basements
- Concrete & Masonry Walls

FEATURES AND BENEFITS

- Stops running water immediately
- Non-Shrink, expands as it sets
- Contains no calcium chloride
- Non-Metallic
- Sulfate resistant
- Easily applied
- No Mixing

300 S. Dayton St.
Davison, MI 48423
S1Eonline.com



FAST SETTING CEMENTITIOUS WATERSTOP

DESCRIPTION

Quad-Plug™ is a blend of special cements and admixtures which are designed to instantly stop running water or seepage in all types of concrete and masonry structures.

PACKAGING

Quad-Plug is supplied in a 50 lb. plastic pail.

YIELD

Quad-Plug will yield approximately .45 cu. ft. (787 cu. in.) per pail.

APPLICATION INFORMATION (TO SEAL RUNNING WATER OR LEAKS)

Prepare crack or hole by chipping out loose material to a minimum depth and width of 3/4". Using a rubber gloved hand, place a generous amount of dry Quad-Plug with a smooth, fast motion to active leak, maintaining external pressure for 30 seconds. Repeat until leak stops.

WARRANTY

Quadex™ warrants its products to be free of defects in material and workmanship. Within one year from purchase, if any Quadex product is proven defective, Quadex will replace said product or refund its purchase price at Quadex's sole discretion. Quadex's obligation shall be limited solely to such replacement or refund. There are no other warranties by Quadex, expressed or implied. There is no warranty if Quadex products are used contrary to Quadex's written directions.

PRECAUTIONS

Avoid eye contact or prolonged contact with skin. Wash thoroughly after use. Persons using Quad-Plug should wear necessary eye protection, dust mask and rubber gloves. Read all product labels and technical literature.